



TL-BLYS1

IP 65	IK08	-20°C + 55°C	>0.9PF	CE	⏚	CRI >80	L70 60,000h	LED
----------	------	-----------------	--------	----	---	------------	----------------	-----

Bollard light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L70 @ 60,000 hours)

Body Type: Die cast Aluminium housing, Corrosion & Shock Resistant

Diffuser: PC or Glass

Light Source: Osram 3030

Driver: Meanwell

Input Voltage: 100 - 277V

Driver Protection: Class I

Operating Temperature: - 20°C + 55°C

Beam Angle: 120°

Body Color: Light Black, Dark black or Custom

Dimmable: 1-10V & Dali

On Request: Other Wattage & Dimension Variants



Templux Lighting s.r.l, Via Gradenigo 58, PD35100, Italy, info@templuxitaly.com, www.templuxitaly.com



TL-BLYS1-01



TL-BLYS1-02



TL-BLYS1-03



TL-BLYS1-04

Product Variants

Product Code	Wattage	CRI	Efficiency	CCT	Size H x D (mm)
TL-BLYS1-01-(10W/25W/35W)	10W / 25W / 35W	80	100 lm/W	3000K/6500K	1016 H x 165 Φ
TL-BLYS1-02-(10W/25W/35W)	10W / 25W / 35W	80	100 lm/W	3000K/6500K	1016 H x 165 Φ
TL-BLYS1-03-(10W/25W/35W)	10W / 25W / 35W	80	100 lm/W	3000K/6500K	999 H x 165 Φ
TL-BLYS1-04-(10W/25W/35W)	10W / 25W / 35W	80	100 lm/W	3000K/6500K	999 H x 165 Φ

