



TL-PLBL



Backlit Panel light ceiling Recessed /Surface/ suspended fixture. Fitting manufactured according to the EN/IEC 60598-1:2015 rules.

Longer life (L70 @ 60,000 hours)

Body Type: CRCA Sheet Steel

Diffuser: Opal Diffuser

Light Source: Tridonic or Equivalent

Driver: Tridonic, Philips or Equivalent

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 10°C + 45°C

Beam Angle: 110°

Body Color: White

IP Rating: IP20, IP40, IP44, IP54, IP65

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali & IGBT

On Request: Other Wattage & Dimension Variants



**PHILIPS
TRIDONIC**



Templux Lighting s.r.l, Via Gradenigo 58, PD35100, Italy, info@templuxitaly.com, www.templuxitaly.com



Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Dimension (LxWxH)
TL-PLBL-30-6060	30W	3450lm	115 -130 lm/W	3000K/6500K	595x595x55
TL-PLBL-36-6060	36W	4150lm	115 - 130 lm/W	3000K/6500K	595x595x55
TL-PLBL-40-6060	40W	4800lm	115 - 130 lm/W	3000K/6500K	595x595x55
TL-PLBL-30-1230	30W	3450lm	115 - 130 lm/W	3000K/6500K	1159x295x55
TL-PLBL-36-1230	36W	4150lm	115 - 130 lm/W	3000K/6500K	1159x295x55
TL-PLBL-40-1230	40W	4800lm	115 - 130 lm/W	3000K/6500K	1159x295x55

