



## TL-PL



Panel light ceiling Recessed /Surface/ suspended fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L70 @ 60,000 hours)

Body Type: Aluminium

Diffuser: PMMA

Light Source: Tridonic or Equivalent

Driver: Tridonic, Philips or Equivalent

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 10°C + 45°C

Beam Angle: 120°

Body Color: White

IP Rating: IP20, IP40, IP44, IP54, IP65

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali & IGBT

On Request: Other Wattage & Dimension Variants



**PHILIPS  
TRIDONIC**



Templux Lighting s.r.l, Via Gradenigo 58, PD35100, Italy, [info@templuxitaly.com](mailto:info@templuxitaly.com), [www.templuxitaly.com](http://www.templuxitaly.com)



## Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Dimension (LxWxH)
TL-PL-33-6060	33W	3800lm	100 -130 lm/W	3000K/6500K	595x595x10
TL-PL-60-6060	60W	6000lm	100 - 130 lm/W	3000K/6500K	595x595x10
TL-PL-40-1230	40W	4000lm	100 - 130 lm/W	3000K/6500K	1159x295x10
TL-PL-60-1230	60W	6000lm	100 - 130 lm/W	3000K/6500K	1159x295x10
TL-PL-60-1260	60W	6000lm	100 - 130 lm/W	3000K/6500K	1159x595x10
TL-PL-20-6060	24W	2800lm	100 - 130 lm/W	3000K/6500K	595x595x10

Acc: 112 - Springs for Recessed non-surface mounting on Plasterboard

Acc: 113 - Suspension Kit

Acc: 114 - Surface Mounting Kit

