



TL-DLFM1



Recessed Mounted downlight light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L70 @ 60,000 hours)

Body Type: Aluminium Die Cast

Diffuser: PC

Light Source: SMD Philips or Equivalent

Driver: Philips, Tridonic or Equivalent

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 10°C + 45°C

Beam Angle: 90°

Frame Color: White or Black

IP Rating: IP40, IP44

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants



PHILIPS
TRIDONIC
CREE



TL-DLFM1-01



TL-DLFM1-02



Product Variants

Product Code	Wattage(W)	Lumen(lm)	Efficiency	CCT	Size /Cutout (mm)	
					TL-DLFM1-01	TL-DLFM1-02
TL-DLFM1-01/02 -6	6W	600lm	100 lm/W	3000K/6500K	Φ90*40 / 80mm	90*90*H40 /80*80
TL-DLFM1-01/02 -12	12W	1200lm	100 lm/W	3000K/6500K	Φ110*48 /100mm	125*125*H53 /110*110
TL-DLFM1-01 -15	15W	1500lm	100 lm/W	3000K/6500K	Φ140*53 / 125mm	
TL-DLFM1-01/02 -18	18W	1800lm	100 lm/W	3000K/6500K	Φ170*53 / 155mm	160*160*H53 /145*145
TL-DLFM1-01/02 -24	24W	2400lm	100 lm/W	3000K/6500K	Φ190*53 / 175mm	190*190*H53 /175*175
TL-DLFM1-01/02 -36	36W	3600lm	100 lm/W	3000K/6500K	Φ215*53 / 200mm	215*215*H53 /200*200

