



## TL-DLFM2



Recessed Mounted Downlight light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L80B20 @ 50,000 hours)

Body Type: Die Cast Aluminium

Diffuser: Opal PC

Light Source: Samsung or Equivalent

Driver: Tridonic, Eaglerise or Equivalent

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Beam Angle: 90°

Body Color: White / Black / Silver

IP Rating: IP20

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants



**SAMSUNG LED**  
**TRIDONIC**  
**EAGLERISE**





## Product Variants

| Product Code | Wattage | Lumen  | Efficiency | CCT           | Beam Angle | Dimension (ØxH) / Cut Out |
|--------------|---------|--------|------------|---------------|------------|---------------------------|
| TL-DLFM2-6W  | 6W      | 540lm  | 90lm/W     | 2700K - 6000K | 90°        | Ø95xH52 / Ø80 mm          |
| TL-DLFM2-12W | 12W     | 1080lm | 90lm/W     | 2700K - 6000K | 90°        | Ø120xH62 / Ø100 mm        |
| TL-DLFM2-15W | 15W     | 1350lm | 90lm/W     | 2700K - 6000K | 90°        | Ø145xH70 / Ø125 mm        |
| TL-DLFM2-18W | 18W     | 1620lm | 90lm/W     | 2700K - 6000K | 90°        | Ø175xH70 / Ø155 mm        |
| TL-DLFM2-24W | 24W     | 2160lm | 90lm/W     | 2700K - 6000K | 90°        | Ø195xH70 / Ø175 mm        |
| TL-DLFM2-36W | 36W     | 3240lm | 90lm/W     | 2700K - 6000K | 90°        | Ø220xH70 / Ø200 mm        |

