



TL-DLFM3



Recessed Mounted Downlight light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L80B20 @ 50,000 hours)

Body Type: Die Cast Aluminium

Diffuser: Opal PC

Light Source: Samsung or Equivalent

Driver: Tridonic, Eaglerise or Equivalent

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Beam Angle: 90°

Body Color: White / Black / Silver

IP Rating: IP20

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants



SAMSUNG LED
TRIDONIC
EAGLERISE





Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Beam Angle	Dimension (ØxH) / Cut Out
TL-DLFM3-6W	6W	510lm	85lm/W	2700K - 6000K	90°	Ø110xH40 / Ø95 mm
TL-DLFM3-9W	9W	765lm	85lm/W	2700K - 6000K	90°	Ø140xH50 / Ø125 mm
TL-DLFM3-15W	15W	1275lm	85lm/W	2700K - 6000K	90°	Ø170xH60 / Ø155 mm
TL-DLFM3-18W	18W	1530lm	85lm/W	2700K - 6000K	90°	Ø190xH70 / Ø175 mm
TL-DLFM3-24W	24W	2040lm	85lm/W	2700K - 6000K	90°	Ø230xH80 / Ø200 mm
TL-DLFM3-36W	36W	3060lm	85lm/W	2700K - 6000K	90°	Ø260xH90 / Ø245 mm

