



TL-DLHNG



Recessed Mounted Downlight light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L70 @ 60,000 hours)

Body Type: Aluminium

Diffuser: Glass

Light Source: Cree or Equivalent

Driver: Tridonic, Philips or Equivalent

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 10°C + 45°C

Beam Angle: 70°, 90° & other angles on Request.

Body Color: White, Black & Silver.

IP Rating: IP40, IP44 & IP54.

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants



PHILIPS
TRIDONIC
CREE 





Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Dimension (LxH)
TL-DLHNG-7	7W	700lm	100lm/W	3000K/6500K	Ø110xH68
TL-DLHNG-10	10W	1000lm	100lm/W	3000K/6500K	Ø110xH68
TL-DLHNG-12	12W	1200lm	100lm/W	3000K/6500K	Ø140xH85
TL-DLHNG-15	15W	1500lm	100lm/W	3000K/6500K	Ø140xH85
TL-DLHNG-25	25W	2500lm	100lm/W	3000K/6500K	Ø190xH109
TL-DLHNG-30	30W	3000lm	100lm/W	3000K/6500K	Ø190xH109

70°

3000K

4000K

