



TL-DLVNA1



Recessed Mounted downlight light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L80 B20 @ 50,000 hours)

Body Type: Aluminium Die Cast

Reflector Finish: Dark Chrome, Shinning Silver, Champaign Gold, Stain Silver

Light Source: Cree or Philips COB

Driver: Philips/Tridonic

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 10°C + 45°C

Beam Angle: 15°, 24°,36°,45°

Frame Color: White/ Black/ Silver

IP Rating: IP44

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants



PHILIPS
TRIDONIC
CREE 





Mounting frame color: White Silver Black



GOLD



MIRROR



DARK CHROME

Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Size /Cutout (mm)
TL-DLVNA01-6	6W	600lm	100 lm/W	2700K/6500K	Φ115*78mm / 102
TL-DLVNA01-10	10W	1000lm	100 lm/W	2700K/6500K	Φ115*78mm / 102
TL-DLVNA01-15	15W	1500lm	100 lm/W	2700K/6500K	Φ115*98mm / 102
TL-DLVNA01-25	25W	2500lm	100 lm/W	2700K/6500K	Φ150*146mm / 160
TL-DLVNA01-30	30W	3000lm	100 lm/W	2700K/6500K	Φ180*160mm / 166
TL-DLVNA01-40	40W	4000lm	100 lm/W	2700K/6500K	Φ180*160mm / 166

