



## TL-FLLA



Flood light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L90 @ 100,000 hours)

Body Type: Aluminium

Diffuser: Tempered Glass

Light Source: Cree

Driver: Meanwell, Philips or Equivalent

MacAdam: 3

Input Voltage: AC 220 - 240V

Driver Protection: Class I

Operating Temperature: - 20°C + 60°C

Beam Angle: 30° ASN / 55° ASW / 120°

Body Color: Grey

Dimmable: Dali

On Request: Other Wattage & Dimension Variants





### Product Varian

Product Code	Wattage	Lumen	Efficiency	CCT	Dimension (mm)
TL-FLLA-48	48W	7000 lm	145 lm/W	3000K/5700K	300x447x32
TL-FLLA-58	58W	9500 lm	163 lm/W	3000K/5700K	300x447x32
TL-FLLA-71	71W	11350 lm	162 lm/W	3000K/5700K	300x447x32
TL-FLLA-96	96W	14000 lm	145 lm/W	3000K/5700K	300x447x32
TL-FLLA-144	144W	21000 lm	145 lm/W	3000K/5700K	396x447x35
TL-FLLA-200	200W	28000 lm	140 lm/W	3000K/5700K	396x447x35

