



TL-FLZSL1



Flood light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L70 @ 60,000 hours)

Body Type: Die cast Aluminium

Diffuser: PC or Glass

Light Source: Philips

Driver: Meanwell

Input Voltage: AC 85 - 277V

Driver Protection: Class I

Operating Temperature: - 20°C + 60°C

Beam Angle: 90°/120°

Body Color: Black / Grey or Custom

Dimmable: 1-10V & Dali

On Request: Other Wattage & Dimension Variants





Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Dimension (LxWxH)
TL-FLZSL1-100	100W	13000 lm	130lm/W	3000K/6500K	380x380x175
TL-FLZSL1-200	200W	26000 lm	130lm/W	3000K/6500K	453x325x190
TL-FLZSL1-300	300W	39000 lm	130lm/W	3000K/6500K	590x335x200
TL-FLZSL1-400	400W	52000 lm	130lm/W	3000K/6500K	590x335x200
TL-FLZSL1-500	500W	65000 lm	130lm/W	3000K/6500K	700x320x200
TL-FLZSL1-600	600W	78000 lm	130lm/W	3000K/6500K	700x320x200

