



TL-GRYS1



Ground Recessed mounted fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L70 @ 60,000 hours)

Body Type: Die cast aluminium & Stainless Steel ring

Diffuser: Tempered Glass

Light Source: Philips, Cree or Equivalent

Driver: Meanwell or Equivalent

Input Voltage: 220 - 240V

Driver Protection: Class I

Operating Temperature: - 20°C to + 55°C

Beam Angle: 10°, 15°, 30°, 60°.

Body Color: Black RAL9005

Dimmable: Dali

On Request: Other Wattage & Dimension Variants





Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Dimension (DxH)
TL-GRYS1-03	3W	300lm	100 lm/W	3000K/6500K	100Φ x 86H mm
TL-GRYS1-06	6W	600lm	100 lm/W	3000K/6500K	153Φ x 93H mm
TL-GRYS1-09	9W	900lm	100 lm/W	3000K/6500K	180Φ x 93H mm
TL-GRYS1-12	12W	1200lm	100 lm/W	3000K/6500K	200Φ x 97H mm
TL-GRYS1-18	18W	1800lm	100 lm/W	3000K/6500K	250Φ x 92H mm

