



## TL-LISHNG



Decorative Suspended Fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L70 @ 50,000 hours)

Body Type: Aluminium

Diffuser: Aluminium Reflector + Lens

Light Source: Osram

Driver: Osram, 3AAA or Equivalent

Input Voltage: 220 - 240V

Driver Protection: Class I

Operating Temperature: - 20°C to + 40°C

Beam Angle: 80° Upper Beam & 45° Lower Beam

Body Color: White / Black / or any other colors on Request

On Request: Other Wattage & Dimension Variants



# OSRAM





UP AND DOWN LINEAR LIGHT

Product Variants

Product Code	Wattage	Lumen	Beam Angle	CCT	Dimension (MM)
TL-LISHNG1-25W	25W	2000lm	UPPER 80° & LOWER 45°	2700K - 5700K	L1200 *W22 *H100 MM
TL-LISHNG1-30W	30W	2400lm	UPPER 80° & LOWER 45°	2700K - 5700K	L1800 *W22 *H100 MM
TL-LISHNG1-35W	35W	2800lm	UPPER 80° & LOWER 45°	2700K - 5700K	L2400 *W22 *H100 MM





### Product Variants

Product Code	Wattage	Lumen	Beam Angle	CCT	Dimension (MM)
TL-LISHNG2-30W	30W	2400lm	50° 80°	2700K - 5700K	L1500 *W22 *H25 MM





### Product Variants

Product Code	Wattage	Lumen	Beam Angle	CCT	Dimension (MM)
TL-LISHNG3-30W	30W	2400lm	50° 80°	2700K - 5700K	L1500 *W22 *H25 MM

