



TL-SPFMA



Recessed Mounted Spot light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L80 B20 @ 50,000 hours)

Body Type: Aluminium Die Cast

Diffuser: PC

Light Source: Cree COB or Equivalent

Driver: Tridonic, Eaglerise or Equivalent

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 10°C + 45°C

Frame Color: White or Black

IP Rating: IP20

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants



PHILIPS
TRIDONIC
CREE 





TL-SPFMA-02



TL-SPFMA-05



TL-SPFMA-03



TL-SPFMA-06



TL-SPFMA-08




TL-SPFMA-07


Product Variants

Product Code	Wattage	Lumen	Beam Angle	CCT	Dimension (DxH) / Cut out (mm)
TL-SPFMA-02-3W	3W	170lm	15°	3000K-6000K	Ø36xH54 / Ø30mm
TL-SPFMA-05-6W	6W	510lm	24°	3000K-6000K	Ø36xH68 / Ø30mm
TL-SPFMA-06-7W	7W	570lm	38°	3000K-6000K	Ø55xH70 / Ø50mm
TL-SPFMA-08-7W	7W	570lm	38°	3000K-6000K	55x55xH70 / 50mm
TL-SPFMA-07-10W	10W	830lm	38°	3000K-6000K	Ø68xH62 / 60mm
TL-SPFMA-03-3W	3W	240lm	38°,45°	3000K-6000K	Ø55xH45 / 46mm


3W 15°



6W 24°



3W 38/45°



CREE 7W 3000K

