



TL-TRLHNG



Track light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L80B20 @ 50,000 hours)

Body Type: Aluminium

Diffuser: Pc

Light Source: Cree or Equivalent

Driver: Tridonic, Philips or Equivalent

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 10°C + 45°C

Beam Angle: 15°,24°,38° & other on Request.

Body Color: White or Black

IP Rating: IP20

Dimmable: Dali

On Request: Other Wattage & Dimension Variants



PHILIPS
TRIDONIC
CREE 





Various optional adaptor

Provide 2/3/4 wire adaptor
match different track system
to the global market



Die-casting aluminium heat sink,
make the better cooling for LED

Select the high level of Cree LED with high lumen,
lumen maintenance and color rendering index

Use high-temperated durable and flame-
retardant LED holder to protect LED chip

Optical reflector with high efficiency up to 90%

High class acrylic to improve the transmitting efficiency

Aluminium baffle available in various color finish

Aluminium adjustable ring change the viewing angle

Adjustable Viewing angle



Product Variants

Product Code	Wattage	Lumen	Beam Angle	CCT	Dimension
TL-TRLHNG-25	25W	2500 lm	15°, 24°, 38°	3000K-6500K	D95 X 152MM
TL-TRLHNG-35	35W	3500 lm	15°, 24°, 38°	3000K-6500K	D104 X 160MM
TL-TRLHNG-40	40W	4000 lm	15°, 24°, 38°	3000K-6500K	D104 X 163MM

