



TL-WPSL



Waterproof Surface or suspended light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L90B10 @ 72,000 hours)

Body: Grey Aluminium Profile

Diffuser: Frosted Tempered Glass

Led Source: Tridonic or Equivalent

Led Standards: IEC62031, IEC62471, IEC62778, IEC62717, IEC61547 , ENEC11

Driver: Tridonic or Equivalent

Driver Standards: EN 55015, EN 61000-3-2, EN 61000-3-3, EN61347-1, ENEC11

MacAdam: 3

Operating Temperature: - 10°C + 55°C

Beam Angle: 115°

Body Color: Grey

Impact Protection: IK10

Emergency Kit: Tridonic

Dimmable: Dali

On Request: Other Wattage & Dimension Variants



powered by

TRIDONIC



Templux Lighting s.r.l, Via Gradenigo 58, PD35100, Italy, info@templuxitaly.com, www.templuxitaly.com



Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Dimension (LxWxH)
TL-WPS1 -15	15W	2000lm	130 lm/W	3000K- 6500K	630x100x90MM
TL-WPS1 -20	20W	2600lm	130 lm/W	3000K- 6500K	630x100x90MM
TL-WPS2- 35	35W	3850lm	110 lm/W	3000K- 6500K	1100x105x75MM
TL-WPS2- 45	45W	4950lm	110 lm/W	3000K- 6500K	1100x105x75MM
TL-WPS3- 50	50W	6500lm	130 lm/W	3000K- 6500K	1100x105x75MM
TL-WPS3- 60	60W	7800lm	130 lm/W	3000K- 6500K	1530x105x75MM

