



## TL-WPZH



Waterproof ceiling or wall or suspended surface fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L80 @ 60,000 hours / L80 @100,000 hours)

TL-WPZH1 - GRP Body & PC/PMMA Diffuser

TL-WPZH2 - PC Body & Diffuser

TL-WPZH3 - Aluminium Body & PC Diffuser Light

Source/Driver: Tridonic, Philips or Equivalent

MacAdam: 3

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 10°C + 55°C

Beam Angle: 115°

Body Color: Grey

Impact Protection: IK08

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants





**TL-WPZH1**  
**TL-WPZH2**



**TL-WPZH3**

### Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Dimension (LxWxH)
TL-WPZH 1/2-44	44W	6100lm	140 lm/W	4000K	1573x101x84MM
TL-WPZH 1/2-53	53W	8200lm	155 lm/W	4000K	1573x101x84MM
TL-WPZH 1/2-72	72W	10000lm	140 lm/W	4000K	1573x101x84MM
TL-WPZH 3-44	44W	6100lm	140 lm/W	4000K	1500x87x70MM
TL-WPZH 3-53	53W	8200lm	155 lm/W	4000K	1500x87x70MM
TL-WPZH 3-72	72W	10000lm	140 lm/W	4000K	1500x87x70MM

