



TL-WWHN1



Wall Washer light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L80B20 @ 50,000 hours)

Body Type: Aluminium Alloy body

Diffuser: Tempered Glass

Light Source: Cree or Equivalent

Input Voltage: 220 - 240V

Driver Protection: Class I

Operating Temperature: - 20°C + 55°C

Beam Angle: 3°, 5°, Customized

Body Color: Grey/Graphite / Black / Customized

On Request: Other Wattage & Dimension Variants



Templux Lighting s.r.l, Via Gradenigo 58, PD35100, Italy, info@templuxitaly.com, www.templuxitaly.com

TL-WWHN1-01



TL-WWHN1-02



TL-WWHN1-03



TL-WWHN1-04



Product Variants

Product Code	Wattage	Beam Angle	CCT	Dimension LxWxH (MM)
TL-WWHN1-01	5W	3°, 5°	2700K, 3000K, 4000K, 6000K	112x60.5x71MM
TL-WWHN1-02	8W	3°, 5°	2700K, 3000K, 4000K, 6000K	152x60.5x71MM
TL-WWHN1-03	10W	3°, 5°	2700K, 3000K, 4000K, 6000K	192x60.5x71MM
TL-WWHN1-04	13W	3°, 5°	2700K, 3000K, 4000K, 6000K	231x60.5x71MM

