



TL-DLFMIP



Recessed Mounted IP rated Downlight light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L90B10 @ 50,000 hours)

Body Type: Die Cast Aluminium

Diffuser: Opal PC

Light Source: Cree or Equivalent

Driver: Tridonic, Eaglerise or Equivalent

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Body Color: White / Black

Reflector color: Chrome/ White/ Black

IP Rating: IP44, IP54, IP65

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants



PHILIPS
TRIDONIC
CREE 





Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Beam Angle	Dimension (ØxH) / Cut Out
TL-DLFMIP-10W	10W	1000lm	100lm/W	2700K - 6000K	15°,20°,36°,55°	Ø110xH65 / Ø100 mm
TL-DLFMIP-15W	15W	1500lm	100lm/W	2700K - 6000K	15°,20°,36°,55°	Ø110xH65 / Ø100 mm
TL-DLFMIP-20W	20W	2000lm	100lm/W	2700K - 6000K	15°,20°,36°,55°	Ø150xH85 / Ø135 mm
TL-DLFMIP-25W	25W	2500lm	100lm/W	2700K - 6000K	15°,20°,36°,55°	Ø150xH85 / Ø135 mm
TL-DLFMIP-30W	30W	3000lm	100lm/W	2700K - 6000K	15°,20°,36°,55°	Ø150xH85 / Ø135 mm
TL-DLFMIP-35W	35W	3500lm	100lm/W	2700K - 6000K	15°,20°,36°,55°	Ø215xH105 / Ø200 mm
TL-DLFMIP-40W	40W	4000lm	100lm/W	2700K - 6000K	15°,20°,36°,55°	Ø215xH105 / Ø200 mm
TL-DLFMIP-45W	45W	4500lm	100lm/W	2700K - 6000K	15°,20°,36°,55°	Ø215xH105 / Ø200 mm
TL-DLFMIP-50W	50W	5000lm	100lm/W	2700K - 6000K	15°,20°,36°,55°	Ø215xH105 / Ø200 mm

