



TL-PNFM2



Suspended led pendant light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L80B10 @ 50,000 hours)

Body Type: Die Cast Aluminium

Ceiling Mounting Plate: Steel Sheet

Light Source: Cree or Equivalent

Driver: Tridonic, Philips or Equivalent

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 10°C + 45°C

Body Color: White, Black

IP Rating: IP20

On Request: Other Wattage & Dimension Variants



PHILIPS
TRIDONIC
CREE 





TL-PNFM2A



TL-PNFM2B
120° Adjustable

Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Beam Angle	Dimension (ØxH)
TL-PNFM2A-10W	10W	1000lm	100lm/W	2700K - 6000K	38°	Ø68xH1200 MM
TL-PNFM2A-20W	20W	2000lm	100lm/W	2700K - 6000K	38°	Ø95xH1200 MM
TL-PNFM2A-30W	30W	3000lm	100lm/W	2700K - 6000K	38°	Ø148xH1200 MM
TL-PNFM2A-40W	40W	4000lm	100lm/W	2700K - 6000K	38°	Ø148xH1200 MM
TL-PNFM2B-10W	10W	1000lm	100lm/W	2700K - 6000K	10°,23°,38°	Ø80xH1200 MM
TL-PNFM2B-20W	20W	2000lm	100lm/W	2700K - 6000K	10°,23°,38°	Ø120xH1200 MM
TL-PNFM2B-30W	30W	3000lm	100lm/W	2700K - 6000K	10°,23°,38°	Ø140xH1200 MM

