



TL-SPFM5



Recessed Mounted Spot light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L90B10 @ 50,000 hours)

Body Type: Die Cast Aluminium Diffuser: PC

Light Source: Philips, Cree or Equivalent

Driver: Tridonic, Eaglerise or Equivalent

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Beam Angle: 38°

Body Color: White / Black / Gold / Copper

IP Rating: IP20

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants



PHILIPS
TRIDONIC
CREE 



A - WHITE



B - BLACK



C - GOLD



D - COPPER

Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Beam Angle	Dimension (ØxH) / Cut Out
TL-SPFM5-3W	3W	300lm	100lm/W	2700K - 6000K	38°	Ø35xH52 / Ø30 mm
TL-SPFM5-5W	5W	500lm	100lm/W	2700K - 6000K	38°	Ø55xH100 / Ø45 mm
TL-SPFM5-10W	10W	1500lm	100lm/W	2700K - 6000K	38°	Ø75xH105 / Ø65mm
TL-SPFM5-15W	15W	1500lm	100lm/W	2700K - 6000K	38°	Ø92xH110 / Ø80 mm
TL-SPFM5-25W	25W	2500lm	100lm/W	2700K - 6000K	38°	Ø128xH130 / Ø110 mm
TL-SPFM5-35W	35W	3500lm	100lm/W	2700K - 6000K	38°	Ø150xH140 / Ø140 mm

