



TL-HBKH



Industrial & Commercial Highbay fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (A - L90B10 @ 100,000 hours) (B - L90B10 @ 50,000 hours)

Body Type: Die cast aluminium

Light Source: Philips Lumileds 3030,5050 150 lm/W.

Driver: Mean Well, Philips or Invertronics

Chromaticity tolerance (MacAdam) : 3

Input Voltage: 100 - 277V

Driver Protection: Class I

Operating Temperature: - 20°C + 55°C

Beam Angle: 60°, 90° & 120°.

Body Color: Black, Grey

Dimmable: 1-10V & Dali

Sensor: Microwave Sensor/ Sensor with Remote Control

On Request: Other Wattage & Dimension Variants





Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Dimension (MM)
TL-HBKH-70- A/B	70W	9400 lm	135lm/W	3000K/6000K	280X250MM
TL-HBKH-100- A/B	100W	15000 lm	150lm/W	3000K/6000K	280X250MM
TL-HBKH-150- A/B	150W	22500 lm	150lm/W	3000K/6000K	320X250MM
TL-HBKH-200- A/B	200W	30000 lm	150lm/W	3000K/6000K	380X250MM

Acc: 101 - Microwave Sensor,1-10V, PWM, Resistance Dimming Function.

Acc: 102 - Microwave Sensor with Remote Control 1-10V, PWM, Resistance Dimming Function MAX 20M.

