



TL-HBKH3



Canopy light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (A - L90B10 @ 100,000 hours) (B - L90B10 @ 50,000 hours)

Body Type: Aluminium

Diffuser: PC

Light Source: Cree or Philips

Driver: Meanwell, Inventronics, Philips or Equivalent

Chromaticity tolerance (MacAdam) : 3

Input Voltage: AC 220 - 265V

SPD: 6KV, 10KV, 20KV

Driver Protection: Class I

Operating Temperature: - 20°C + 50°C

Beam Angle: 30°, 60°, 120°

Body Color: Black / White

Dimmable: Dali, 1-10V Optional

On Request: Other Wattage & Dimension Variants



Surface



Product Variants

Product Code	Wattage	Lumen	Beam Angle	CCT	Dimension (mm)
TL-HBKH3-01-30 - A/B	30W	4500 lm	60°,120°	3000K-6500K	200x200x84
TL-HBKH3-01-50 -A/B	50W	7500 lm	30°,60°,120°	3000K-6500K	245x245x84
TL-HBKH3-01-100 -A/B	100W	15000 lm	30°,60°,120°	3000K-6500K	266x266x95
TL-HBKH3-1A-30 -A/B	30W	3000 lm	60°,120°	3000K-6500K	200x200x36
TL-HBKH3-1A-50 -A/B	50W	5000 lm	30°,60°,120°	3000K-6500K	245x245x36
TL-HBKH3-1A-100 -A/B	100W	10000 lm	30°,60°,120°	3000K-6500K	266x266x46



Recessed



Product Variants

Product Code	Wattage	Lumen	Beam Angle	CCT	Dimension (mm)
TL-HBKH3-02-30 - A/B	30W	4500 lm	60°,120°	3000K-6500K	200x200x84
TL-HBKH3-02-50 -A/B	50W	7500 lm	30°,60°,120°	3000K-6500K	245x245x84
TL-HBKH3-02-100 -A/B	100W	15000 lm	30°,60°,120°	3000K-6500K	266x266x95
TL-HBKH3-2A-30 -A/B	30W	3000 lm	60°,120°	3000K-6500K	200x200x32
TL-HBKH3-2A-50 -A/B	50W	5000 lm	30°,60°,120°	3000K-6500K	245x245x32
TL-HBKH3-2A-100 -A/B	100W	10000 lm	30°,60°,120°	3000K-6500K	266x266x42



Suspended



Product Variants

Product Code	Wattage	Lumen	Beam Angle	CCT	Dimension (mm)
TL-HBKH3-03-30 - A/B	30W	4500 lm	60°,120°	3000K-6500K	200x200x122
TL-HBKH3-03-50 -A/B	50W	7500 lm	30°,60°,120°	3000K-6500K	245x245x122
TL-HBKH3-03-100 -A/B	100W	15000 lm	30°,60°,120°	3000K-6500K	266x266x134
TL-HBKH3-3A-30 -A/B	30W	3000 lm	60°,120°	3000K-6500K	200x200x42
TL-HBKH3-3A-50 -A/B	50W	5000 lm	30°,60°,120°	3000K-6500K	245x245x42
TL-HBKH3-3A-100 -A/B	100W	10000 lm	30°,60°,120°	3000K-6500K	266x266x52

