



TL-DLKH2



Recessed Mounted downlight light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L90B10 @ 50,000 hours)

Body Type: High Purity Aluminium

Light Source: COB

Driver: Lifud, Eaglerise, Tridonic or Equivalent

Chromaticity tolerance (MacAdam) : 3

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 10°C + 40°C

Beam Angle: 10°, 23°, 36°

Frame Color: White, Black

Reflector Color: Black, Silver

IP Rating: IP40

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants



PHILIPS
TRIDONIC
CREE 





TL-DLKH2A



TL-DLKH2B

Product Variants

Product Code	Wattage	Lumen	Beam Angle	CCT	Size /Cutout (mm)
TL-DLKH2A-01-7W	7W	700lm	10°, 23°, 36°	2700K - 6500K	Φ65*53H / 55 mm
TL-DLKH2A-01-12W	12W	1200lm	10°, 23°, 36°	2700K - 6500K	Φ85*62H / 75 mm
TL-DLKH2A-01-18W	18W	1800lm	10°, 23°, 36°	2700K - 6500K	Φ105*77H / 95 mm
TL-DLKH2B-02-7W	7W	700lm	10°, 23°, 36°	2700K - 6500K	65L*65W*53H / 55*55mm
TL-DLKH2B-02-12W	12W	1200lm	10°, 23°, 36°	2700K - 6500K	85L*85W*62H / 75*75mm
TL-DLKH2B-02-18W	18W	1800lm	10°, 23°, 36°	2700K - 6500K	105L*105W*77H / 95*95mm



TL-DLKH2C



TL-DLKH2D



TL-DLKH2E

Product Variants

Product Code	Wattage	Lumen	Beam Angle	CCT	Size /Cutout (mm)
TL-DLKH2C-03-2*7W	14W	1400lm	10°, 23°, 36°	2700K - 6500K	126L*65W*53H / 115*55mm
TL-DLKH2C-03-2*12W	24W	2400lm	10°, 23°, 36°	2700K - 6500K	160L*75W*62H / 150*65mm
TL-DLKH2C-03-2*18W	36W	3600lm	10°, 23°, 36°	2700K - 6500K	208L*105W*77H / 195*95
TL-DLKH2D-04-3*7W	21W	2100lm	10°, 23°, 36°	2700K - 6500K	182L*65W*53H / 175*55
TL-DLKH2D-04-3*12W	36W	3600lm	10°, 23°, 36°	2700K - 6500K	252L*85W*62H / 240*75
TL-DLKH2E-04-4*7W	28W	2800lm	10°, 23°, 36°	2700K - 6500K	126L*126W*53H / 115*115
TL-DLKH2E-04-4*12W	48W	4800lm	10°, 23°, 36°	2700K - 6500K	165L*165W*62H / 155*155

