



TL-DLKH3



Recessed Mounted downlight light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L90B10 @ 50,000 hours)

Body Type: High Purity Aluminium

Light Source: COB /SMD

Driver: Lifud, Eaglerise, Tridonic or Equivalent

Chromaticity tolerance (MacAdam) : 3

Input Voltage: 220-265V AC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 10°C + 40°C

Beam Angle: 60° COB, 110° SMD

Frame Standard Color: White, Other Color on Request

IP Rating: IP65 Fitting + IP65 Driver
IP65 Fitting + IP20 Driver

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT





Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Size /Cutout (mm)
TL-DLKH3-7W	7W	700lm	120 lm/W	2700K - 6500K	Φ90*67H/ 75-88
TL-DLKH3-10W	10W	1200lm	120 lm/W	2700K - 6500K	Φ90*67H/ 75-88
TL-DLKH3-12W	12W	1440lm	120 lm/W	2700K - 6500K	Φ108*72H /95-100
TL-DLKH3-16W	16W	1920lm	120 lm/W	2700K - 6500K	Φ140*72H /95-130
TL-DLKH3-24W	24W	2880lm	120 lm/W	2700K - 6500K	Φ190*70H / 160-180
TL-DLKH3-30W	30W	3600lm	120 lm/W	2700K - 6500K	Φ240*70H / 206-225
TL-DLKH3-35W	35W	4200lm	120 lm/W	2700K - 6500K	Φ240*70H / 206-225





Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Size /Cutout (mm)
TL-DLKH3B-7W	7W	700lm	120 lm/W	2700K - 6500K	Φ90*67H/ 75-88
TL-DLKH3B-10W	10W	1200lm	120 lm/W	2700K - 6500K	Φ90*67H/ 75-88
TL-DLKH3B-12W	12W	1440lm	120 lm/W	2700K - 6500K	Φ108*72H /95-100
TL-DLKH3B-16W	16W	1920lm	120 lm/W	2700K - 6500K	Φ140*72H /95-130
TL-DLKH3B-24W	24W	2880lm	120 lm/W	2700K - 6500K	Φ190*70H / 160-180
TL-DLKH3B-30W	30W	3600lm	120 lm/W	2700K - 6500K	Φ240*70H / 206-225
TL-DLKH3B-35W	35W	4200lm	120 lm/W	2700K - 6500K	Φ240*70H / 206-225

