



TL-DLKH4



Recessed Mounted downlight light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L90B10 @ 50,000 hours)

Body Type: High Purity Aluminium

Light Source: COB

Driver: Lifud, Eaglerise, Tridonic or Equivalent

Chromaticity tolerance (MacAdam) : 3

Input Voltage: 220-265V AC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 10°C + 40°C

Beam Angle: 24°, 38°

Frame Standard Color: White, Other Color on Request

Reflector Color: White/Silver/Black

IP Rating: IP40

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants



PHILIPS
TRIDONIC
CREE 




Adjustable



Product Variants

Product Code	Wattage	Beam Angle	Lumen	Efficiency	CCT	Size /Cutout (mm)
TL-DLKH4-3W	3W	24° , 38°	300lm	100 lm/W	2700K - 6500K	Φ65*70H/ 55 mm
TL-DLKH4-5W	5W	24° , 38°	500lm	100 lm/W	2700K - 6500K	Φ65*70H/ 55 mm
TL-DLKH4-9W	9W	24° , 38°	900lm	100 lm/W	2700K - 6500K	Φ85*75H/ 75 mm
TL-DLKH4-15W	15W	24° , 38°	1500lm	100 lm/W	2700K - 6500K	Φ105*100H/ 95 mm

