



## TL-DLKH7



Recessed Mounted downlight light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L90B10 @ 50,000 hours)

Body Type: High Purity Aluminium

Light Source: SMD

Driver: Lifud, Eaglerise, Tridonic or Equivalent

Chromaticity tolerance (MacAdam) : 3

Input Voltage: 220-265V AC 50/60HZ

Driver Protection: Class I

Frame Color: White

IP Rating: IP40

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants



**PHILIPS**  
**TRIDONIC**  
**CREE** 





## Product Variants

| Product Code     | Wattage | Lumen  | Beam Angle | CCT           | Size /Cutout (mm) |
|------------------|---------|--------|------------|---------------|-------------------|
| TL-DLKH7A-01-7W  | 7W      | 700lm  | 120°       | 2700K - 6500K | Φ94*40H / 75mm    |
| TL-DLKH7A-02-12W | 12W     | 1200lm | 120°       | 2700K - 6500K | Φ120*40H / 100mm  |
| TL-DLKH7A-03-18W | 18W     | 1800lm | 120°       | 2700K - 6500K | Φ145*40H / 125mm  |
| TL-DLKH7A-04-24W | 24W     | 2400lm | 120°       | 2700K - 6500K | Φ175*40H / 155mm  |
| TL-DLKH7A-05-30W | 30W     | 3000lm | 120°       | 2700K - 6500K | Φ220*40H / 200mm  |
| TL-DLKH7A-06-33W | 33W     | 3300lm | 120°       | 2700K - 6500K | Φ220*40H / 200mm  |





## Product Variants

| Product Code     | Wattage | Lumen  | Beam Angle | CCT           | Size /Cutout (mm)    |
|------------------|---------|--------|------------|---------------|----------------------|
| TL-DLKH7B-01-7W  | 7W      | 700lm  | 120°       | 2700K - 6500K | 94*94*40H / 75*75    |
| TL-DLKH7B-02-12W | 12W     | 1200lm | 120°       | 2700K - 6500K | 120*120*40H /100*100 |
| TL-DLKH7B-03-18W | 18W     | 1800lm | 120°       | 2700K - 6500K | 145*145*40H /125*125 |
| TL-DLKH7B-04-24W | 24W     | 2400lm | 120°       | 2700K - 6500K | 175*175*40H /155*155 |
| TL-DLKH7B-05-30W | 30W     | 3000lm | 120°       | 2700K - 6500K | 220*220*40H /200*200 |
| TL-DLKH7B-06-33W | 33W     | 3300lm | 120°       | 2700K - 6500K | 220*220*40H /200*200 |





## Product Variants

| Product Code     | Wattage | Lumen  | Beam Angle | CCT           | Size /Cutout (mm) |
|------------------|---------|--------|------------|---------------|-------------------|
| TL-DLKH7C-01-7W  | 7W      | 700lm  | 120°       | 2700K - 6500K | Φ90*28H / 80mm    |
| TL-DLKH7C-02-16W | 16W     | 1600lm | 120°       | 2700K - 6500K | Φ120*28H / 110mm  |
| TL-DLKH7C-03-24W | 24W     | 2400lm | 120°       | 2700K - 6500K | Φ170*28H / 160mm  |
| TL-DLKH7C-04-32W | 32W     | 3200lm | 120°       | 2700K - 6500K | Φ225*28H / 210mm  |





## Product Variants

| Product Code     | Wattage | Lumen  | Beam Angle | CCT           | Size /Cutout (mm)    |
|------------------|---------|--------|------------|---------------|----------------------|
| TL-DLKH7D-01-7W  | 7W      | 700lm  | 120°       | 2700K - 6500K | 90*90*28H / 80*80    |
| TL-DLKH7D-02-16W | 16W     | 1600lm | 120°       | 2700K - 6500K | 120*120*28H /110*110 |
| TL-DLKH7D-03-24W | 24W     | 2400lm | 120°       | 2700K - 6500K | 170*170*28H /160*160 |
| TL-DLKH7D-04-32W | 32W     | 3200lm | 120°       | 2700K - 6500K | 225*225*28H /210*210 |

