



## TL-DLKH8



Recessed Mounted downlight light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L90B10 @ 50,000 hours)

Body Type: High Purity Aluminium

Light Source: SMD

Driver: Lifud, Eaglerise, Tridonic or Equivalent

Chromaticity tolerance (MacAdam) : 3

Input Voltage: 220-265V AC 50/60HZ

Driver Protection: Class I

Frame Color: White, Black

IP Rating: IP40

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants



**PHILIPS**  
**TRIDONIC**  
**CREE** 





## Product Variants

Product Code	Wattage	Lumen	Beam Angle	CCT	Size /Cutout (mm)
TL-DLKH8A-01-7W	7W	700lm	120°	2700K - 6500K	Φ90*50H / 70mm
TL-DLKH8A-02-10W	10W	1000lm	120°	2700K - 6500K	Φ105*53H / 85mm
TL-DLKH8A-03-15W	15W	1500lm	120°	2700K - 6500K	Φ120*62H / 100mm
TL-DLKH8A-04-20W	20W	2000lm	120°	2700K - 6500K	Φ160*73H / 140mm
TL-DLKH8A-05-30W	30W	3000lm	120°	2700K - 6500K	Φ190*82H / 170mm
TL-DLKH8A-06-40W	40W	4000lm	120°	2700K - 6500K	Φ220*95H / 200mm





### Product Variants

Product Code	Wattage	Lumen	Beam Angle	CCT	Size /Cutout (mm)
TL-DLKH8B-01-7W	7W	700lm	120°	2700K - 6500K	Φ83*50H / 75mm
TL-DLKH8B-02-12W	12W	1200lm	120°	2700K - 6500K	Φ104*63H / 95mm
TL-DLKH8B-03-18W	18W	1800lm	120°	2700K - 6500K	Φ123*74H / 115mm

