



TL-SMCYNW



Surface Mounted downlight light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L90B10 @ 50,000 hours)

Body Type: Aluminium Die Cast

Diffuser: PC in White / Black / Specular Silver Reflector Choice

Light Source: Cree, Samsung

Driver: Philips, Eaglerise or Equivalent

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 5°C + 50°C

Beam Angle: 54°

Finish: White, Black, Grey

IP Rating: IP65

Optional Dali Dimmable Driver



PHILIPS
TRIDONIC
CREE 



IP65 WATERPROOF

The IP65 is designed for use in humid spaces. Suitable for indoor and outdoor use.



Product Variants

Product Code	Wattage(W)	Lumen(lm)	Efficiency	CCT	Beam Angle	Size (D*H)mm
TL-SMCYNW-01	7W	700lm	100 lm/W	3000K/6000K	12°,24°,36°	85*H80
TL-SMCYNW-02	12W	1200lm	100 lm/W	3000K/6000K	12°,24°,36°	85*H80
TL-SMCYNW-03	15W	1500lm	100 lm/W	3000K/6000K	12°,24°,36°	96*H150
TL-SMCYNW-04	24W	2400lm	100 lm/W	3000K/6000K	12°,24°,36°	96*H150
TL-SMCYNW-05	30W	3000lm	100 lm/W	3000K/6000K	12°,24°,36°	142*H160

