



TL-SMKH1



Surface Mounted downlight light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L90B10 @ 50,000 hours)

Body Type: Aluminium Die Cast

Diffuser: PC in White / Black / Specular Silver Reflector Choice

Light Source: Cree, Samsung

Driver: Lifud, Tridonic or Equivalent

Chromaticity tolerance (MacAdam) : 3

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 5°C + 50°C

Finish: White, Black

IP Rating: TL-SMKH1B Series - IP40, IP44, IP54, IP65

TL-SMKH1A Series & TL-SMKH1C Series -IP40

Optional Dali Dimmable Driver





Product Variants

Product Code	Wattage(W)	Lumen(lm)	Efficiency	CCT	Beam Angle	Size (D*H)mm
TL-SMKH1A-01	10W	1000lm	100 lm/W	2700K - 6000K	15°,30°,45°	76*76*H150
TL-SMKH1A-02	15W	1500lm	100 lm/W	2700K - 6000K	15°,30°,45°	76*76*H150
TL-SMKH1A-03	20W	2000lm	100 lm/W	2700K - 6000K	15°,30°,45°	96*96*H150
TL-SMKH1A-04	25W	2500lm	100 lm/W	2700K - 6000K	15°,30°,45°	116*116*H150
TL-SMKH1A-05	30W	3000lm	100 lm/W	2700K - 6000K	15°,30°,45°	116*116*H150





Product Variants

Product Code	Wattage(W)	Lumen(lm)	Efficiency	CCT	Beam Angle	Size (D*H)mm
TL-SMKH1B-01	10W	1000lm	100 lm/W	2700K - 6000K	15°,30°,45°	76*H150
TL-SMKH1B-02	15W	1500lm	100 lm/W	2700K - 6000K	15°,30°,45°	76*H150
TL-SMKH1B-03	20W	2000lm	100 lm/W	2700K - 6000K	15°,30°,45°	96*H150
TL-SMKH1B-04	30W	3000lm	100 lm/W	2700K - 6000K	15°,30°,45°	116*H150
TL-SMKH1B-05	40W	4000lm	100 lm/W	2700K - 6000K	15°,30°,45°	142*H160
TL-SMKH1B-06	50W	5000lm	100 lm/W	2700K - 6000K	15°,30°,45°	171*H180





5spots



10spots



15spots

Product Variants

Product Code	Wattage(W)	Lumen(lm)	Efficiency	CCT	Beam Angle	Size (D*H)mm
TL-SMKH1C-01	10W	1000lm	100 lm/W	2700K - 6000K	15°,30°,45°	136*50*H45
TL-SMKH1C-02	20W	2000lm	100 lm/W	2700K - 6000K	15°,30°,45°	269*50*H45
TL-SMKH1C-03	30W	3000lm	100 lm/W	2700K - 6000K	15°,30°,45°	402*50*H45

