



## TL-SMKH2



Surface Mounted downlight light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L90B10 @ 50,000 hours)

Body Type: Aluminium Die Cast

Diffuser: PC in White

Light Source: Cree, Samsung

Driver: Lifuid, Eaglerise or Equivalent

Chromaticity tolerance (MacAdam) : 3

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 5°C + 50°C

Finish: White, Black

IP Rating: IP40

Optional Dali Dimmable Driver



**PHILIPS**  
**TRIDONIC**  
**CREE**





## Product Variants

Product Code	Wattage(W)	Lumen(lm)	Efficiency	CCT	Beam Angle	Size (D*H)mm
TL-SMKH2B-01	6W	600lm	100 lm/W	2700K - 6000K	110°	90*90*H55
TL-SMKH2B-02	12W	1200lm	100 lm/W	2700K - 6000K	110°	120*120*H55
TL-SMKH2B-03	18W	1800lm	100 lm/W	2700K - 6000K	110°	180*180*H55
TL-SMKH2B-04	24W	2400lm	100 lm/W	2700K - 6000K	110°	220*220*H55
TL-SMKH2B-05	36W	3600lm	100 lm/W	2700K - 6000K	110°	300*300*H55





### Product Variants

Product Code	Wattage(W)	Lumen(lm)	Efficiency	CCT	Beam Angle	Size (D*H)mm
TL-SMKH2A-01	6W	600lm	100 lm/W	2700K - 6000K	110°	90*H55
TL-SMKH2A-02	12W	1200lm	100 lm/W	2700K - 6000K	110°	120*H55
TL-SMKH2A-03	18W	1800lm	100 lm/W	2700K - 6000K	110°	180*H55
TL-SMKH2A-04	24W	2400lm	100 lm/W	2700K - 6000K	110°	220*H55
TL-SMKH2A-05	30W	3000lm	100 lm/W	2700K - 6000K	110°	300*H55
TL-SMKH2A-06	34W	3400lm	100 lm/W	2700K - 6000K	110°	300*H55

