



# TL-SPHNG



Recessed Mounted Spot light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L80 B10 @ 50,000 hours)

Body Type: Aluminium Die Cast

Diffuser: PC

Light Source: Cree COB or Equivalent

Driver: Tridonic, Eaglerise or Equivalent

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 10°C + 45°C

Frame Color: White or Black

IP Rating: IP20, IP40

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants



**PHILIPS**  
**TRIDONIC**  
**CREE** 





**TL-SPHNG 2A, 2B**




**TL-SPHNG 2C**




**Product Variants**


Product Code	Wattage	Lumen	Beam Angle	CCT	Dimension (DxH) / Cut out (mm)
TL-SPHNG2A-1W	1W	100 lm	36°	2700K-6000K	Ø20xH30 / Ø 17mm
TL-SPHNG2B-1W	1W	100 lm	15°	2700K-6000K	Ø30xH40 / Ø 25mm
TL-SPHNG2C-3W	3W	300 lm	15°, 24°, 36°	2700K-6000K	Ø45xH51 / Ø 40mm




h(m)	E(lx)	D(m)
1	847	Ø0.28
2	211	Ø0.57
3	94	Ø0.85
4	53	Ø1.14
5	33	Ø1.42




h(m)	E(lx)	D(m)
1	216	Ø0.60
2	54	Ø1.20
3	24	Ø1.80
4	13	Ø2.40
5	8	Ø3.00



h(m)	E(lx)	D(m)
1	908	Ø0.40
2	227	Ø0.80
3	100	Ø1.20
4	56	Ø1.60
5	36	Ø2.00



h(m)	E(lx)	D(m)
1	823	Ø0.43
2	205	Ø0.86
3	91	Ø1.30
4	51	Ø1.73
5	32	Ø2.16



h(m)	E(lx)	D(m)
1	666	Ø0.47
2	166	Ø0.94
3	74	Ø1.41
4	41	Ø1.88
5	26	Ø2.35

