



TL-SPKH2



Recessed Mounted Spot light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L90 B10 @ 50,000 hours)

Body Type: Aluminium Die Cast

Diffuser: PC

Light Source: Cree COB or Equivalent

Driver: Tridonic, Lifud, Eaglerise or Equivalent

Chromaticity tolerance (MacAdam) : 3

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Reflector Color: White/Silver/Black/Matt Black/Golden

Frame Color: White or Black

IP Rating: IP65 Fitting + IP65 Driver

IP65 Fitting + IP20 Driver

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants






Adjustable

Product Variants

Product Code	Wattage	Lumen	Beam Angle	CCT	Dimension /Cutout (mm)
TL-SPKH2A-01-5W	5W	500lm	15°24°36°60°	2700K-6500K	63φx69 H mm / 55 mm
TL-SPKH2A-01-7W	7W	700lm	15°24°36°60°	2700K-6500K	63φx69 H mm / 55 mm
TL-SPKH2A-01-10W	10W	1000lm	15°24°36°60°	2700K-6500K	85φx74 H mm / 75 mm
TL-SPKH2A-01-15W	15W	1500lm	15°24°36°60°	2700K-6500K	110φx83 H mm / 95 mm
TL-SPKH2A-01-20W	20W	2000lm	15°24°36°60°	2700K-6500K	110φx83 H mm / 95 mm

