



TL-SPKH3



Recessed Mounted Spot light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L90 B10 @ 50,000 hours)

Body Type: Aluminium Die Cast

Diffuser: PC

Light Source: Cree COB or Equivalent

Driver: Tridonic, Lifud, Eaglerise or Equivalent

Chromaticity tolerance (MacAdam) : 3

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 10°C + 45°C

Frame Color: White or Black

IP Rating: IP40

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants



PHILIPS
TRIDONIC
CREE 



TL-SPKH3-01-2W



TL-SPKH3-02-6W



TL-SPKH3-03-8W



TL-SPKH3-04-10W



TL-SPKH3-05-16W



TL-SPKH3-06-18W



TL-SPKH3-07-20W



TL-SPKH3-08-30W



TL-SPKH3-09-36W





Product Variants

Product Code	Wattage	Lumen	Beam Angle	CCT	Dimension /Cutout (mm)
TL-SPKH3-01-2W	2W	200lm	12° 24° 38° 50° 50x50° 70x70° 35x70°	2700K-6500K	55x54x49mm / 45*45 mm
TL-SPKH3-02-6W	4W	400lm		2700K-6500K	131x54x49mm / 120*45 mm
TL-SPKH3-03-8W	8W	800lm		2700K-6500K	92x92x49mm / 82*82 mm
TL-SPKH3-04-10W	10W	1000lm		2700K-6500K	207x54x49mm / 195*45 mm
TL-SPKH3-05-16W	16W	1600lm		2700K-6500K	169x92x49mm / 157*82 mm
TL-SPKH3-06-18W	18W	1800lm		2700K-6500K	131x131x49mm / 119*119mm
TL-SPKH3-07-20W	20W	2000lm		2700K-6500K	397x54x49mm / 388*45 mm
TL-SPKH3-08-30W	30W	3000lm		2700K-6500K	588x54x49mm / 577*45 mm
TL-SPKH3-09-36W	36W	3600lm		2700K-6500K	246x132x49mm / 234*120mm

