



TL-SPPS



Recessed Mounted Spot light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L70 @ 60,000 hours)

Body Type: Aluminium

Diffuser: Glass

Light Source: Cree or Equivalent

Driver: Tridonic, Philips or Equivalent

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 10°C + 45°C

Beam Angle: 15°, 24°, 38°, 60° & other on Request.

Body Color: White, White with Gold, Black & Silver.

IP Rating: IP40, IP43.

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants



PHILIPS
TRIDONIC
CREE 



Templux Lighting s.r.l, Via Gradenigo 58, PD35100, Italy, info@templuxitaly.com, www.templuxitaly.com

TL-SPPS-01

WHITE + GOLD



TL-SPPS-02 WHITE

TL-SPPS-03 BLACK

TL-SPPS-04 SILVER



Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Dimension (D) mm
TL-SPPS-(01/02/03/04)-3	3W	300lm	100lm/W	3000K/6500K	Ø70, Cut out:55
TL-SPPS-(01/02/03/04)-5	5W	500lm	100lm/W	3000K/6500K	Ø90, Cut out:75
TL-SPPS-(01/02/03/04)-10	10W	1000lm	100lm/W	3000K/6500K	Ø110, Cut out:95
TL-SPPS-(01/02/03/04)-15	15W	1500lm	100lm/W	3000K/6500K	Ø138, Cut out:120
TL-SPPS-(01/02/03/04)-20	20W	2000lm	100lm/W	3000K/6500K	Ø138, Cut out:120

