



TL-SPVNA2



Recessed Mounted Spot light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L80 B20 @ 50,000 hours)

Body Type: Aluminium Die Cast

Reflector : Aluminium Reflector

Light Source: Cree or Philips COB

Driver: Eagle rise or Equivalent

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 10°C + 45°C

Beam Angle: 20°, 25°, 40°

Frame Color: White/ Black/ Silver

IP Rating: IP44

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants



PHILIPS
TRIDONIC
CREE 

EAGLE RISE



TL-SPVNA02-01



Mounting frame color: White Silver Black

TL-SPVNA02-02



Mounting frame color: White Silver Black
0° - 30° on Vertical Plane, 358° on Horizontal Plane

TL-SPVNA02-03



Mounting frame color: White Silver Black
0° - 30° on Vertical Plane, 358° on Horizontal Plane

TL-SPVNA02-04



Mounting frame color: White Silver Black

TL-SPVNA02-05



TL-SPVNA02-06



Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Size /Cutout (mm)
TL-SPVNA02-01	6W	600lm	100 lm/W	2700K/6500K	Φ65*40mm / 58mm
TL-SPVNA02-02	3W	300lm	100 lm/W	2700K/6500K	Φ58*22mm / 50mm
TL-SPVNA02-03	3W	300lm	100 lm/W	2700K/6500K	Φ58*32mm / 50mm
TL-SPVNA02-04	3W	300lm	100 lm/W	2700K/6500K	Φ48*22mm / 43mm
TL-SPVNA02-05	2W	200lm	100 lm/W	2700K/6500K	Φ32*38mm / 27mm
TL-SPVNA02-06	1W	100lm	100 lm/W	2700K/6500K	Φ32*22mm / 27mm

