



TL-SPVNTL02



Recessed Mounted Spot light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L80 B20 @ 50,000 hours)

Body Type: Aluminium Die Cast

Light Source: Cree COB or Equivalent

Driver: Tridonic, Philips or Equivalent

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 10°C + 45°C

Reflector color: Gold, Mirror, White, Dark Chrome, Black

Frame color: White, Silver, Black

IP Rating: IP44

Emergency Kit: Tridonic

Dimmable: 1-10V, Dali, IGBT

On Request: Other Wattage & Dimension Variants



PHILIPS
TRIDONIC
CREE 





Product Variants

Product Code	Wattage	Lumen	Beam Angle	CCT	Dimension (DxH) / Cut out (mm)
TL-SPVNTL02-10W	10W	910lm	10°, 13°, 24°, 36°, 50°	2700K-4000K	Ø110xH108 / Ø102mm
TL-SPVNTL02-15W	15W	1300lm	10°, 13°, 24°, 36°, 50°	2700K-4000K	Ø110xH108 / Ø102mm
TL-SPVNTL01-20W	20W	1800lm	10°, 13°, 24°, 36°, 50°	2700K-4000K	Ø110xH108 / Ø102mm

