



## TL-TRLKH



Track light fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L90B10 @ 50,000 hours)

Body Type: Aluminium

Diffuser: PC

Light Source: Cree or Equivalent

Driver: Tridonic, Lifuid or Equivalent

Chromaticity tolerance (MacAdam) : 3

Input Voltage: 220-240VAC 50/60HZ

Driver Protection: Class I

Operating Temperature: - 10°C + 45°C

Beam Angle: 24°,36° & other on Request.

Body Color: White, Black & Other colors on Request

IP Rating: IP20

Dimmable: Dali

On Request: Other Wattage & Dimension Variants



**PHILIPS**  
**TRIDONIC**  
**CREE** 



Templux Lighting s.r.l, Via Gradenigo 58, PD35100, Italy, [info@templuxitaly.com](mailto:info@templuxitaly.com), [www.templuxitaly.com](http://www.templuxitaly.com)



350°



90°

## Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Dimension
TL-TRLKH-5	5W	500 lm	100lm/W	3000K/6500K	D50 X 128MM
TL-TRLKH-10	10W	1000 lm	100lm/W	3000K/6500K	D50 X 128MM
TL-TRLKH-20	20W	2000 lm	100lm/W	3000K/6500K	D60 X 145MM
TL-TRLKH-30	30W	3000 lm	100lm/W	3000K/6500K	D70 X 155MM
TL-TRLKH-40	40W	4000 lm	100lm/W	3000K/6500K	D80 X 175MM

