



TL-WPKH



Weatherproof Ceiling or wall or Suspended fixture. Fitting manufactured according to the EN / IEC 60598-1:2015 rules.

Longer life (L90B10 @ 50,000 hours)

Body / Diffuser : PC

Light Source: Bridgelux or Philips or Tridonic

Efficiency: 100 lm /W as Standard. 120 lm /W, 140 lm /W on Request

Driver: Lifud , Tridonic or Equivalent

Chromaticity tolerance (MacAdam) : 3

Input Voltage: 200- 240V, 50-60 HZ

Driver Protection: Class I

Operating Temperature: - 20°C + 55°C

Beam Angle: 120°.

Body Color Standard: Dark grey

Customized Colors: White / Black

Dimmable: 1-10V & Dali

Sensor: Microwave Sensor





Product Variants

Product Code	Wattage	Lumen	Efficiency	CCT	Dimension (AXBXC)
TL-WPKH-20	20W	2000 lm	100lm/W	3000K/6000K	600X74X71MM
TL-WPKH-30	30W	3000 lm	100lm/W	3000K/6000K	900X74X71MM
TL-WPKH-40	40W	4000 lm	100lm/W	3000K/6000K	1200X74X71MM
TL-WPKH-50	50W	5000 lm	100lm/W	3000K/6500K	1500X74X71MM

Available with Customized Lumens & wattage for all the above dimensions

